

## Angular Contact Ball Bearing (ZrO2)



seleccionar	Consulta	Número de rodamiento	Dimentions(mm)					Mounting Dimentions(mm)			Reference Weight(kg)
			d	D	B	r(min)	r1(min)	da min	Da max	ra max	
7000	10	26	8	0.3	0.15	12.5	23.5	0.3	0.014		
7900	10	22	6	0.3	0.15	12.5	19.5	0.3	0.007		
7200	10	30	9	0.6	0.3	15	25	0.6	0.025		
7300	10	35	11	0.6	0.3	15	30	0.6	0.04		
7901	12	24	6	0.3	0.15	14.5	21.5	0.3	0.008		
7001	12	28	8	0.3	0.15	14.5	25.5	0.3	0.017		
7201	12	32	10	0.6	0.3	17	27	0.6	0.028		
7301	12	37	12	1	0.6	18	31	1	0.046		
7902	15	28	7	0.3	0.15	17.5	25.5	0.3	0.012		
7002	15	32	9	0.3	0.15	17.5	29.5	0.3	0.024		
7202	15	35	11	0.6	0.3	20	30	0.3	0.035		
7302	15	42	13	1	0.6	21	36	1	0.064		
7903	17	30	7	0.3	0.15	19.5	27.5	0.3	0.013		
7003	17	35	10	0.3	0.15	19.5	32.5	0.3	0.032		
7203	17	40	12	0.6	0.3	22	35	0.6	0.052		
7303	17	47	14	1	0.6	23	41	1	0.087		
7904	20	37	9	0.3	0.15	22.5	34.5	0.3	0.028		
7004	20	42	12	0.6	0.3	25	37	0.6	0.052		
7204	20	47	14	1	0.6	26	41	1	0.082		
7304	20	52	15	1.1	0.6	27	45	1	0.11		
7905	25	42	9	0.3	0.15	27.5	39.5	0.3	0.032		
7005	25	47	12	0.6	0.3	30	42	0.6	0.061		
7205	25	52	15	1	0.6	31	46	1	0.099		
7305	25	62	17	1.1	0.6	32	55	1	0.18		
7906	30	47	9	0.3	0.15	32.5	44.5	1	0.04		
7006	30	55	13	1	0.6	36	49	1	0.089		
7206	30	62	16	1	0.6	36	56	1	0.15		
7306	30	72	19	1.1	0.6	37	65	1	0.27		

### Angular Contact Ball Bearing (ZrO2)

---

7907	35	55	10	0.6	0.3	40	50	0.6	0.058
7007	35	62	14	1	0.6	41	56	1	0.12